

Stapler 92/25-553

12000159



Fastener type

BeA Staples 92
· Length: 10 - 25 mm

Product strengths

- Adjustable depth setting
- Contact release
- Quick release
- Top loaded magazine

Scope of operation

Carpentry, Dry and interior extension, Furniture and frame construction, Joinery, Measurement and assembly construction, Roofing and facade, Wood packaging, Wooden constructions

Scope of delivery

Sparepart list, User manual


More details:



Technical data

EAN	4045759001584
Type of fastener	BeA Staples 92
Fastener length min	10 mm
Fastener length max	25 mm
Magazine capacity max	157 pc
Weight	1,2 kg
Driving system	Compressed air
Activation method	Single activation
Operating pressure min	5 bar
Operating pressure max	6 bar
Air consumption per drive operation	0,45 l (6 bar)
Tool length	228 mm
Tool width	46 mm
Tool height	178 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	78,3 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	82,1 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	2,03 m/s ²
Vibration value Ka according to ISO 8662	0,51 m/s ²
Weight incl. packaging	1,37 kg

Related fastener



BeA Staples 92
· Length: 12 - 25 mm

Item No.	Length	Point type	Material
10000370	21 mm	Chisel point	Steel, galvanized
10001434	21 mm	Chisel point	Steel, galvanized, hard
10001435	25 mm	Chisel point	Steel, galvanized, hard
10002653	12 mm	Chisel point	Steel, galvanized
10002654	15 mm	Chisel point	Steel, galvanized
10002655	18 mm	Chisel point	Steel, galvanized
10002657	25 mm	Chisel point	Steel, galvanized
10002937	21 mm	Chisel point	Steel, galvanized
10003867	18 mm	Chisel point	Steel, galvanized
10005435	25 mm	Chisel point	Steel, galvanized
10005649	25 mm	Chisel point	Steel, galvanized
10005885	12 mm	Chisel point	Steel, galvanized
10005886	15 mm	Chisel point	Steel, galvanized
10005887	18 mm	Chisel point	Steel, galvanized
10005888	25 mm	Chisel point	Steel, galvanized

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website