

Stapler 180/65-835C

12000500



More details:



Fastener type

BeA Staples 180
· Length: 40 - 65 mm

Product strengths

- Contact release
- Easy maintenance

Scope of operation

Carpentry, Prefabricated house construction, Roofing and facade, Timber construction, Timber frame construction, Wooden constructions

Scope of delivery

Sparepart list, User manual

Technical data

| | |
|--|-----------------------|
| EAN | 4045759043355 |
| Type of fastener | BeA Staples 180 |
| Fastener length min | 40 mm |
| Fastener length max | 65 mm |
| Magazine capacity max | 132 pc |
| Weight | 2,7 kg |
| Driving system | Compressed air |
| Activation method | Contact activation |
| Operating pressure min | 6 bar |
| Operating pressure max | 8 bar |
| Air consumption per drive operation | 2,7 l (6 bar) |
| Tool length | 370 mm |
| Tool width | 107 mm |
| Tool height | 328 mm |
| BG eligible for funding | No |
| Declaration of conformity | CE, EAC, UKCA |
| Noise characteristic L pA, 1s according to EN 12549 | 91,4 dB(A) |
| Noise characteristic L WA, 1s, d according to EN 12549 | 93,8 dB(A) |
| Noise characteristic K pA and K WA according to EN 12549 | 2,5 dB(A) |
| Vibration value ahd according to ISO 8662 | 3,07 m/s ² |
| Vibration value Ka according to ISO 8662 | 1,45 m/s ² |
| Weight incl. packaging | 3,3 kg |

Related fastener



BeA Staples 180
· Length: 40 - 65 mm

| Item No. | Length | Point type | Material |
|----------|--------|--------------|--|
| 10000676 | 50 mm | Chisel point | Stainless Steel, (AISI 316, EN grade 1.4401, A4) |
| 10000692 | 63 mm | Chisel point | Stainless Steel, (AISI 316, EN grade 1.4401, A4) |
| 10000697 | 65 mm | Chisel point | Steel, galvanized, hard |
| 10003594 | 63 mm | Chisel point | Steel, galvanized, hard |
| 10003896 | 50 mm | Chisel point | Steel, galvanized, hard |
| 10004800 | 45 mm | Chisel point | Steel, galvanized |
| 10004801 | 63 mm | Chisel point | Steel, galvanized |
| 10004812 | 40 mm | Chisel point | Steel, galvanized |
| 10004813 | 65 mm | Chisel point | Steel, galvanized |
| 10004835 | 45 mm | Chisel point | Steel, galvanized, hard |
| 10004836 | 50 mm | Chisel point | Steel, galvanized |
| 10004837 | 50 mm | Chisel point | Steel, galvanized, hard |
| 10004864 | 55 mm | Chisel point | Steel, galvanized |
| 10004865 | 60 mm | Chisel point | Steel, galvanized |
| 10005360 | 63 mm | Chisel point | Steel, galvanized, hard |
| 10005445 | 56 mm | Chisel point | Steel, galvanized, hard |
| 10005651 | 40 mm | Chisel point | Stainless Steel, (AISI 316, EN grade 1.4401, A4) |
| 10005848 | 45 mm | Chisel point | Steel, galvanized |
| 10005849 | 50 mm | Chisel point | Steel, galvanized |
| 10005850 | 55 mm | Chisel point | Steel, galvanized |

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website