

Brad Nailer SK 335-201

12100004



More details:



Fastener type

BeA Countersunk nails SK 300
· Length: 10 - 35 mm

Product strengths

- Adjustable depth setting
- Adjustable ventilation
- Includes transport case
- Integrated noise reduction
- Long nose

Scope of operation

Dry and interior extension, Joinery, Roofing and facade, Window and door construction, Wooden constructions

Scope of delivery

Hex key, Service Instructions, Sparepart list, Transport case, User manual


Technical data

EAN	4045759004523
Type of fastener	BeA Countersunk nails SK 300
Fastener length min	10 mm
Fastener length max	35 mm
Tool magazin slope	0 °
Magazine capacity max	100 pc
Weight	0,8 kg
Driving system	Compressed air
Activation method	Contact activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	0,46 l (6 bar)
Depth adjustment	Yes
Tool length	254 mm
Tool width	53 mm
Tool height	213 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	80,6 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	87,2 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	3,18 m/s ²

Technical data

Vibration value Ka according to ISO 8662	0,19 m/s ²
Weight incl. packaging	2,16 kg

Related fastener



BeA Countersunk nails SK 300

- Diameter: 1,2 mm
- Length: 10 - 35 mm

Item No.	Diameter x Length	Nail shank	Material
10300261	1,2 mm x 14 mm	Smooth shank	Steel, galvanized
10300268	1,2 mm x 19 mm	Smooth shank	Steel, galvanized
10300337	1,2 mm x 30 mm	Smooth shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)
10300338	1,2 mm x 35 mm	Smooth shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)
10300449	1,2 mm x 10 mm	Smooth shank	Steel, galvanized
10300643	1,2 mm x 15 mm	Smooth shank	Steel, galvanized
10300644	1,2 mm x 20 mm	Smooth shank	Steel, galvanized
10300645	1,2 mm x 25 mm	Smooth shank	Steel, galvanized
10300646	1,2 mm x 30 mm	Smooth shank	Steel, galvanized
10300648	1,2 mm x 35 mm	Smooth shank	Steel, galvanized
10300670	1,2 mm x 16 mm	Smooth shank	Steel, galvanized
10300717	1,2 mm x 32 mm	Smooth shank	Steel, galvanized

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website