

Brad Nailer SK 338-616C

12000225



**Fastener type**

BeA Countersunk nails SK 300  
· Length: 22 - 38 mm

**Scope of operation**

Dry and interior extension, Joinery, Roofing and facade, Window and door construction, Wooden constructions

**Scope of delivery**

Sparepart list, User manual

More details:




**Technical data**

EAN	4045759002246
Type of fastener	BeA Countersunk nails SK 300
Fastener length min	22 mm
Fastener length max	38 mm
Tool magazin slope	0 °
Magazine capacity max	125 pc
Weight	1,6 kg
Driving system	Compressed air
Activation method	Contact activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	0,9 l (6 bar)
Tool length	258 mm
Tool width	57 mm
Tool height	205 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	81 dB(A)
Noise characteristic L WA. 1s, d according to EN 12549	83,6 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	1,63 m/s <sup>2</sup>
Vibration value Ka according to ISO 8662	0,44 m/s <sup>2</sup>

**Technical data**

Weight incl. packaging	1,78 kg
------------------------	---------

## Related fastener



## BeA Countersunk nails SK 300

- Diameter: 1,2 mm
- Length: 25 - 38 mm

Item No.	Diameter x Length	Nail shank	Material
10300337	1,2 mm x 30 mm	Smooth shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)
10300338	1,2 mm x 35 mm	Smooth shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)
10300645	1,2 mm x 25 mm	Smooth shank	Steel, galvanized
10300646	1,2 mm x 30 mm	Smooth shank	Steel, galvanized
10300648	1,2 mm x 35 mm	Smooth shank	Steel, galvanized
10300649	1,2 mm x 38 mm	Smooth shank	Steel, galvanized
10300717	1,2 mm x 32 mm	Smooth shank	Steel, galvanized

**Other variations and sizes on request**

Access all Declarations of Performance (DoPs) and CE-Label on our website