

Brad Nailer SK 350-224C

12000467



Fastener type

BeA Countersunk nails SK 300
· Length: 18 - 50 mm

Scope of operation

Dry and interior extension, Joinery, Roofing and facade, Window and door construction, Wooden constructions

Scope of delivery

Sparepart list, User manual

More details:




Technical data

EAN	4045759004387
Type of fastener	BeA Countersunk nails SK 300
Fastener length min	18 mm
Fastener length max	50 mm
Tool magazin slope	0 °
Magazine capacity max	104 pc
Weight	1,24 kg
Driving system	Compressed air
Activation method	Contact activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	0,9 l (6 bar)
Tool length	248 mm
Tool width	59 mm
Tool height	233 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	88,9 dB(A)
Noise characteristic L WA. 1s, d according to EN 12549	95,4 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	1,5 m/s ²
Vibration value Ka according to ISO 8662	0,7 m/s ²

Technical data

Weight incl. packaging	1,92 kg
------------------------	---------

Related fastener



BeA Countersunk nails SK 300

- Diameter: 1,2 mm
- Length: 19 - 50 mm

Item No.	Diameter x Length	Nail shank	Material
10300268	1,2 mm x 19 mm	Smooth shank	Steel, galvanized
10300337	1,2 mm x 30 mm	Smooth shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)
10300338	1,2 mm x 35 mm	Smooth shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)
10300644	1,2 mm x 20 mm	Smooth shank	Steel, galvanized
10300645	1,2 mm x 25 mm	Smooth shank	Steel, galvanized
10300646	1,2 mm x 30 mm	Smooth shank	Steel, galvanized
10300648	1,2 mm x 35 mm	Smooth shank	Steel, galvanized
10300649	1,2 mm x 38 mm	Smooth shank	Steel, galvanized
10300650	1,2 mm x 40 mm	Smooth shank	Steel, galvanized
10300651	1,2 mm x 45 mm	Smooth shank	Steel, galvanized
10300652	1,2 mm x 50 mm	Smooth shank	Steel, galvanized
10300717	1,2 mm x 32 mm	Smooth shank	Steel, galvanized

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website