

Brad Nailer SKAM 350-226C (26°)

12100233



Fastener type

BeA Countersunk nails SKAM 300
· Length: 20 - 50 mm

Product strengths

- Adjustable depth setting
- Adjustable ventilation
- Contact release
- Includes transport case
- Integrated noise reduction

Scope of operation

Dry and interior extension, Joinery, Roofing and facade, Window and door construction, Wooden constructions

Scope of delivery

Hex key, Service Instructions, Service oil, Sparepart list, Transport case, User manual

More details:




Technical data

EAN	4045759006688
Type of fastener	BeA Countersunk nails SKAM 300
Fastener length min	20 mm
Fastener length max	50 mm
Tool magazin slope	26 °
Magazine capacity max	120 pc
Weight	1,38 kg
Driving system	Compressed air
Activation method	Contact activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	1,4 l (6 bar)
Depth adjustment	Yes
Tool length	227 mm
Tool width	68 mm
Tool height	261 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	88,8 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	96,1 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	2,56 m/s ²

Technical data

Vibration value Ka according to ISO 8662	0,75 m/s ²
Weight incl. packaging	3,48 kg

Related fastener



BeA Countersunk nails SKAM 300

- Diameter: 1,54 mm
- Length: 20 - 50 mm

Item No.	Diameter x Length	Nail shank	Material
10300487	1,54 mm x 20 mm	Smooth shank	Steel, galvanized
10300488	1,54 mm x 25 mm	Smooth shank	Steel, galvanized
10300489	1,54 mm x 32 mm	Smooth shank	Steel, galvanized
10300490	1,54 mm x 38 mm	Smooth shank	Steel, galvanized
10300491	1,54 mm x 45 mm	Smooth shank	Steel, galvanized
10300492	1,54 mm x 50 mm	Smooth shank	Steel, galvanized

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website