

Brad Nailer SKAM 450-227C

12100293



More details:



Fastener type

BeA Countersunk nails SKAM 400
· Length: 25 - 50 mm

Product strengths

- Adjustable depth setting
- Adjustable ventilation
- Contact release
- Includes transport case
- Integrated noise reduction

Scope of operation

Dry and interior extension, Joinery, Roofing and facade, Window and door construction, Wooden constructions

Scope of delivery

Hex key, Service Instructions, Service oil, Sparepart list, Transport case, User manual


Technical data

| | |
|--|--------------------------------|
| EAN | 4045759007272 |
| Type of fastener | BeA Countersunk nails SKAM 400 |
| Fastener length min | 25 mm |
| Fastener length max | 50 mm |
| Tool magazin slope | 26 ° |
| Magazine capacity max | 120 pc |
| Weight | 1,38 kg |
| Driving system | Compressed air |
| Activation method | Contact activation |
| Operating pressure min | 5 bar |
| Operating pressure max | 8 bar |
| Air consumption per drive operation | 1,4 l (6 bar) |
| Depth adjustment | Yes |
| Tool length | 277 mm |
| Tool width | 68 mm |
| Tool height | 261 mm |
| BG eligible for funding | No |
| Declaration of conformity | CE, EAC, UKCA |
| Noise characteristic L pA, 1s according to EN 12549 | 80 dB(A) |
| Noise characteristic L WA, 1s, d according to EN 12549 | 86 dB(A) |
| Noise characteristic K pA and K WA according to EN 12549 | 2,5 dB(A) |
| Vibration value ahd according to ISO 8662 | 3,1 m/s ² |

Technical data

| | |
|------------------------|---------|
| Weight incl. packaging | 3,48 kg |
|------------------------|---------|

Related fastener



BeA Countersunk nails SKAM 400

- Diameter: 1,54 mm
- Length: 32 - 50 mm

| Item No. | Diameter x Length | Nail shank | Material |
|----------|-------------------|--------------|-------------------|
| 10300518 | 1,54 mm x 32 mm | Smooth shank | Steel, galvanized |
| 10300519 | 1,54 mm x 38 mm | Smooth shank | Steel, galvanized |
| 10300520 | 1,54 mm x 45 mm | Smooth shank | Steel, galvanized |
| 10300521 | 1,54 mm x 50 mm | Smooth shank | Steel, galvanized |

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website