

Brad Nailer SKS 650-228C

12100331



Fastener type

BeA Countersunk nails SKS 600
· Length: 18 - 50 mm

Product strengths

- Adjustable depth setting
- Adjustable ventilation
- Includes transport case
- Sequential trigger

Scope of operation

Dry and interior extension, Joinery, Roofing and facade, Window and door construction, Wooden constructions

Scope of delivery

Service oil, Sparepart list, Transport case, User manual

More details:




Technical data

EAN	4045759007654
Type of fastener	BeA Countersunk nails SKS 600
Fastener length min	18 mm
Fastener length max	50 mm
Tool magazin slope	0 °
Magazine capacity max	80 pc
Weight	1,5 kg
Driving system	Compressed air
Activation method	Contact activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	1,4 l (6 bar)
Depth adjustment	Yes
Tool length	245 mm
Tool width	66 mm
Tool height	250 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	86,4 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	97,1 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	2,86 m/s ²

Technical data

Vibration value Ka according to ISO 8662	0,78 m/s ²
Weight incl. packaging	2,46 kg

Related fastener



BeA Countersunk nails SKS 600

- Diameter: 1,8 mm
- Length: 18 - 50 mm

Item No.	Diameter x Length	Nail shank	Material
10300550	1,8 mm x 18 mm	Smooth shank	Steel, galvanized
10300551	1,8 mm x 20 mm	Smooth shank	Steel, galvanized
10300552	1,8 mm x 25 mm	Smooth shank	Steel, galvanized
10300553	1,8 mm x 30 mm	Smooth shank	Steel, galvanized
10300555	1,8 mm x 40 mm	Smooth shank	Steel, galvanized
10300557	1,8 mm x 50 mm	Smooth shank	Steel, galvanized

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website