

Coil Nailer 564DCC

12100510



More details:



Fastener type

- BeA Nails BDC
- Diameter: 2,1 - 2,9 mm
- Length: 38 - 65 mm

Product strengths

- Adjustable ventilation
- Contact release
- Integrated noise reduction

Scope of operation

Carpentry, Industrial packaging, Pallet construction and repair, Prefabricated house construction, Timber construction

Scope of delivery

Sparepart list, User manual


Technical data

EAN	4045759051886
Type of fastener	BeA Nails BDC
Fastener diameter min	2,1 mm
Fastener diameter max	2,9 mm
Fastener length min	38 mm
Fastener length max	65 mm
Tool magazin slope	16 °
Magazine capacity max	1 coil
Weight	2,62 kg
Driving system	Compressed air
Activation method	Contact activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	1,87 l (7 bar)
Tool length	269 mm
Tool width	132 mm
Tool height	315 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	92,6 dB(A)
Noise characteristic L WA. 1s, d according to EN 12549	101 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)

Technical data

Vibration value ahd according to ISO 8662	3,83 m/s ²
Vibration value Ka according to ISO 8662	1,91 m/s ²
Weight incl. packaging	3,6 kg

Related fastener



BeA Nails BDC

- Diameter: 2,1 - 2,8 mm
- Length: 38 - 65 mm

Item No.	Diameter x Length	Nail shank	Material
10500122	2,8 mm x 60 mm	Smooth shank	Steel, bright
10500126	2,8 mm x 60 mm	Ring shank	Steel, bright
10500138	2,8 mm x 65 mm	Ring shank	Steel, galvanized
10500141	2,5 mm x 65 mm	Smooth shank	Steel, bright
10500144	2,8 mm x 65 mm	Smooth shank	Steel, bright
10500146	2,5 mm x 65 mm	Ring shank	Steel, bright
10500227	2,8 mm x 65 mm	Smooth shank	Steel, galvanized
10500240	2,8 mm x 42 mm	Ring shank	Steel, bright
10500259	2,5 mm x 65 mm	Smooth shank	Steel, galvanized
10500280	2,5 mm x 65 mm	Ring shank	Steel, hot-dip galvanized
10500375	2,2 mm x 45 mm	Smooth shank	Steel, bright
10500376	2,2 mm x 50 mm	Smooth shank	Steel, bright
10500377	2,2 mm x 60 mm	Smooth shank	Steel, bright
10500380	2,2 mm x 45 mm	Ring shank	Steel, bright
10500381	2,2 mm x 50 mm	Ring shank	Steel, bright
10500382	2,5 mm x 45 mm	Smooth shank	Steel, bright
10500394	2,1 mm x 45 mm	Clinch	Steel, bright
10500397	2,3 mm x 55 mm	Smooth shank	Steel, bright
10500424	2,5 mm x 60 mm	Ring shank	Steel, bright
10500425	2,5 mm x 65 mm	Ring shank	Steel, bright
10500426	2,2 mm x 55 mm	Smooth shank	Steel, bright
10500429	2,5 mm x 50 mm	Smooth shank	Steel, bright
10500430	2,5 mm x 55 mm	Smooth shank	Steel, bright
10500431	2,5 mm x 60 mm	Smooth shank	Steel, bright
10500434	2,5 mm x 45 mm	Ring shank	Steel, bright
10500435	2,5 mm x 50 mm	Ring shank	Steel, bright
10500436	2,5 mm x 55 mm	Ring shank	Steel, bright
10500437	2,5 mm x 60 mm	Ring shank	Steel, bright

10500442	2,1 mm x 55 mm	Clinch	Steel, bright
10500454	2,5 mm x 60 mm	Smooth shank	Steel, galvanized
10500457	2,5 mm x 45 mm	Ring shank	Steel, galvanized
10500458	2,5 mm x 50 mm	Ring shank	Steel, galvanized
10500459	2,5 mm x 55 mm	Ring shank	Steel, galvanized
10500460	2,5 mm x 60 mm	Ring shank	Steel, galvanized
10500477	2,2 mm x 55 mm	Ring shank	Steel, bright
10500479	2,1 mm x 40 mm	Clinch	Steel, bright
10500487	2,5 mm x 57 mm	Ring shank	Steel, bright
10500634	2,1 mm x 38 mm	Ring shank	Steel, bright
10500637	2,1 mm x 40 mm	Smooth shank	Steel, bright
10500639	2,1 mm x 40 mm	Ring shank	Steel, bright
10500642	2,1 mm x 40 mm	Ring shank	Steel, galvanized
10500644	2,1 mm x 45 mm	Smooth shank	Steel, bright
10500646	2,1 mm x 45 mm	Ring shank	Steel, bright
10500650	2,1 mm x 50 mm	Smooth shank	Steel, bright
10500651	2,1 mm x 50 mm	Clinch	Steel, bright
10500652	2,1 mm x 50 mm	Ring shank	Steel, bright
10500653	2,1 mm x 50 mm	Ring shank	Steel, galvanized
10500654	2,1 mm x 55 mm	Smooth shank	Steel, bright
10500656	2,1 mm x 55 mm	Ring shank	Steel, bright
10500803	2,1 mm x 40 mm	Clinch	Steel, bright
10500820	2,5 mm x 50 mm	Ring shank	Steel, bright
10500822	2,5 mm x 55 mm	Ring shank	Steel, bright
10500825	2,5 mm x 60 mm	Screw shank	Steel, bright
10500827	2,5 mm x 65 mm	Screw shank	Steel, bright
10500868	2,5 mm x 40 mm	Ring shank	Steel, bright
10500954	2,5 mm x 55 mm	Screw shank	Steel, bright
10500955	2,5 mm x 60 mm	Screw shank	Steel, bright
10500957	2,8 mm x 65 mm	Screw shank	Steel, bright
10500977	2,5 mm x 50 mm	Screw shank	Steel, bright
10501146	2,5 mm x 65 mm	Screw shank	Steel, bright
10501220	2,2 mm x 55 mm	Screw shank	Steel, bright
10501258	2,8 mm x 65 mm	Ring shank	Steel, bright
10501271	2,5 mm x 65 mm	Ring shank	Steel, galvanized
10501363	2,5 mm x 55 mm	Screw shank	Steel, bright
10501467	2,5 mm x 60 mm	Ring shank	Steel, bright
10501487	2,1 mm x 45 mm	Ring shank	Steel, bright
10501490	2,5 mm x 55 mm	Ring shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)

10501494	2,5 mm x 65 mm	Ring shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)
10501546	2,8 mm x 65 mm	Ring shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)
10501714	2,3 mm x 60 mm	Smooth shank	Steel, bright
10501717	2,3 mm x 40 mm	Ring shank	Steel, bright
10501718	2,3 mm x 45 mm	Ring shank	Steel, bright
10501719	2,3 mm x 50 mm	Ring shank	Steel, bright
10501720	2,3 mm x 55 mm	Ring shank	Steel, bright
10501722	2,3 mm x 55 mm	Screw shank	Steel, bright
10501724	2,5 mm x 42 mm	Ring shank	Steel, bright
10502023	2,8 mm x 50 mm	Screw shank	Steel, bright
10502024	2,8 mm x 57 mm	Screw shank	Steel, bright
10502075	2,1 mm x 45 mm	Ring shank	Steel, galvanized
10502223	2,65 mm x 38 mm	Ring shank	Steel, bright
10502269	2,15 mm x 55 mm	Smooth shank	Steel, bright
10502278	2,2 mm x 50 mm	Ring shank	Steel, bright
10502299	2,5 mm x 55 mm	Smooth shank	Steel, bright

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website