

Anchor Nailer R60-943E

12100436



Fastener type

- BeA Anchor nails R20°
- Diameter: 4 mm
- Length: 40 - 60 mm

Product strengths

- Adjustable ventilation
- Includes transport case
- Precise hole finding due to optimised nose
- Rear loaded magazine
- Sequential trigger

Scope of operation

Carpentry, Roofing and facade, Timber frame construction

Scope of delivery

Sparepart list, Transport case, User manual

More details:




Technical data

EAN	4045759044987
Type of fastener	BeA Anchor nails R20°
Fastener diameter min	4 mm
Fastener diameter max	4 mm
Fastener length min	40 mm
Fastener length max	60 mm
Magazine capacity max	25 pc
Weight	2,5 kg
Driving system	Compressed air
Activation method	Single activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	1,73 l (7 bar)
Tool length	325 mm
Tool width	360 mm
Tool height	97 mm
BG eligible for funding	Yes
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	96,2 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	104 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	4,41 m/s ²

Technical data

Vibration value Ka according to ISO 8662	2,21 m/s ²
Weight incl. packaging	4,9 kg

Related fastener



BeA Anchor nails R20°
· Diameter: 4 mm
· Length: 40 - 60 mm

Item No.	Diameter x Length	Nail shank	Material
10401172	4 mm x 40 mm	Anchor	Steel, galvanized
10401173	4 mm x 50 mm	Anchor	Steel, galvanized
10401174	4 mm x 60 mm	Anchor	Steel, galvanized

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website