

Strip Nailer D34/100-934C

12100234



More details:



Fastener type

- BeA Nails D34
- Diameter: 2,5 - 3,4 mm
- Length: 50 - 100 mm

Product strengths

- Adjustable depth setting
- Adjustable ventilation
- Integrated noise reduction
- Pusher stop
- Switchable from single to contact release

Scope of operation

Carpentry, Formwork construction, Pallet construction and repair, Roofing and facade, Timber construction, Timber frame construction, Wood packaging, Wooden constructions

Scope of delivery

Hex key, Service Instructions, Sparepart list, User manual

Technical data

EAN	4045759006695
Type of fastener	BeA Nails D34
Fastener diameter min	2,5 mm
Fastener diameter max	3,4 mm
Fastener length min	50 mm
Fastener length max	100 mm
Tool magazin slope	34 °
Magazine capacity max	90 pc
Weight	3,42 kg
Driving system	Compressed air
Activation method	Single activation / Contact activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	3,3 l (6 bar)
Depth adjustment	Yes
Tool length	500 mm
Tool width	114 mm
Tool height	360 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	90 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	100 dB(A)

Technical data

Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	3,9 m/s ²
Vibration value Ka according to ISO 8662	0,88 m/s ²
Weight incl. packaging	7,02 kg

Related fastener



BeA Nails D34

- Diameter: 2,9 - 3,4 mm
- Length: 50 - 100 mm

Item No.	Diameter x Length	Nail shank	Material
10400561	2,9 mm x 70 mm	Smooth shank	Steel, bright
10400562	3,1 mm x 83 mm	Smooth shank	Steel, bright
10400563	3,1 mm x 90 mm	Smooth shank	Steel, bright
10400564	3,4 mm x 90 mm	Smooth shank	Steel, bright
10400565	3,4 mm x 100 mm	Smooth shank	Steel, bright
10400567	3,1 mm x 83 mm	Smooth shank	Steel, galvanized
10400568	3,1 mm x 90 mm	Smooth shank	Steel, galvanized
10400570	3,4 mm x 100 mm	Smooth shank	Steel, galvanized
10400571	2,9 mm x 50 mm	Ring shank	Steel, bright
10400573	2,9 mm x 76 mm	Ring shank	Steel, bright
10400574	3,1 mm x 83 mm	Ring shank	Steel, bright
10400575	3,1 mm x 90 mm	Ring shank	Steel, bright
10400576	3,1 mm x 100 mm	Ring shank	Steel, bright
10400578	3,1 mm x 83 mm	Ring shank	Steel, galvanized
10400579	2,9 mm x 50 mm	Ring shank	Steel, hot-dip galvanized
10400581	2,9 mm x 76 mm	Ring shank	Steel, hot-dip galvanized
10400582	3,1 mm x 90 mm	Ring shank	Steel, hot-dip galvanized
10400583	3,1 mm x 100 mm	Ring shank	Steel, hot-dip galvanized
10400589	2,9 mm x 70 mm	Ring shank	Steel, bright
10400597	3,1 mm x 90 mm	Ring shank	Steel, galvanized
10400626	2,9 mm x 80 mm	Smooth shank	Steel, bright
10400627	3,1 mm x 90 mm	Smooth shank	Steel, hot-dip galvanized
10400630	2,9 mm x 70 mm	Smooth shank	Steel, galvanized
10400746	2,9 mm x 76 mm	Ring shank	Steel, galvanized
10400776	2,9 mm x 80 mm	Ring shank	Steel, bright
10400817	2,9 mm x 65 mm	Smooth shank	Steel, bright
10400818	2,9 mm x 65 mm	Ring shank	Steel, bright
10400819	2,9 mm x 65 mm	Ring shank	Steel, hot-dip galvanized

10400820	2,9 mm x 65 mm	Smooth shank	Steel, galvanized
10400821	2,9 mm x 65 mm	Ring shank	Steel, galvanized

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website