

Strip Nailer R20/130-1303E

12100694



More details:



Fastener type

- BeA Nails R20
- Diameter: 3,8 - 4,2 mm
- Length: 90 - 130 mm

Product strengths

- Additional handle
- Integrated noise reduction
- Pusher stop

Scope of operation

Carpentry, Formwork construction, Pallet construction and repair, Roofing and facade, Timber construction, Timber frame construction, Wood packaging, Wooden constructions

Scope of delivery

Additional handhold, Sparepart list, User manual


Technical data

EAN	4045758119990
Type of fastener	BeA Nails R20
Fastener diameter min	3,8 mm
Fastener diameter max	4,2 mm
Fastener length min	90 mm
Fastener length max	130 mm
Tool magazin slope	20 °
Magazine capacity max	56 pc
Weight	6,52 kg
Driving system	Compressed air
Activation method	Single activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	3,3 l (6 bar)
Depth adjustment	Yes
Tool length	560 mm
Tool height	492 mm
BG eligible for funding	Yes
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	97,5 dB(A)
Noise characteristic L WA. 1s, d according to EN 12549	103,6 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)

Technical data

Vibration value ahd according to ISO 8662	6,1 m/s ²
Vibration value Ka according to ISO 8662	1,1 m/s ²
Weight incl. packaging	5,8 kg

Related fastener



BeA Nails R20

- Diameter: 3,8 - 4,2 mm
- Length: 100 - 130 mm

Item No.	Diameter x Length	Nail shank	Material
10400060	3,8 mm x 110 mm	Smooth shank	Steel, bright
10400062	3,8 mm x 120 mm	Smooth shank	Steel, bright
10400064	3,8 mm x 120 mm	Screw shank	Steel, bright
10400065	3,8 mm x 130 mm	Smooth shank	Steel, galvanized
10400067	3,8 mm x 130 mm	Smooth shank	Steel, bright
10400068	4,2 mm x 130 mm	Smooth shank	Steel, bright
10400077	3,8 mm x 100 mm	Smooth shank	Steel, bright
10400197	3,8 mm x 120 mm	Smooth shank	Steel, galvanized
10400462	3,8 mm x 130 mm	Ring shank	Steel, bright
10400463	3,8 mm x 130 mm	Screw shank	Steel, bright

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website