



BeA 

CE

For brads type
SKDA 600

BeA Cordless Nailer SKDA664-650E

- Light and well balanced
- Angled magazine allows easy access into difficult corners
- Ergonomic handgrip
- Rear loading
- Rafter hook
- Depth adjustment
- No-mark-nose for sensitive surfaces
- Quick release
- Single shot actuation
- High performance battery
- Indicator light for battery charge
- For brads type SKDA from 32 - 64 mm

Applications

Interior fittings, furniture industry, window production, corner bonds, prefabricate house industry, wood ceilings



BeA 

SPEED. POWER. RELIABILITY.

BeA SKDA664-650E


Technical Data



Item code	12100518
EAN-No.	4045759048732
Magazine type	Rear loader
Safety system	Single shot
Fastener type	SKDA 600 34°
Nail length	32 - 64 mm
Magazine capacity	100 nails
Nails per strip	94 nails per strip
Shots per second	2 - 3 shots / sec
Shot limit	500 shots / hour
Charging time of battery	120 min.
Battery voltage	6 Volt
Shots per battery charge	up to 4.000
Shots per fuel cell	up to 1.100
Dimension L/W/H, mm	320 / 134 / 305
Weight	2,3 kg
Emission sound pressure level at the workstation	$L_{pA, 1s, d} = 87,0 \text{ dB}$
Single shot emission sound pressure level	$L_{WA, 1s, d} = 89,7 \text{ dB}$
Vibration level as per ISO 8662-11 is	1,93 m/s ² .
Supplied accessories	Sturdy case, two high capacity batteries, charger, safety glasses, instruction manual

Subject to technical modifications

Countersunk head nails, SKDA 600 34°



Diameter	1.8 mm
Length	32 - 64 mm
Material	NK = steel, electro- galvanized, service class 2 RF = stainless steel, comparable to material 1.4301
Surface property	HZ = Steel, resin coated to attain higher withdrawal values
Shank property	Smooth

Joh. Friedrich Behrens AG
Industrielle Befestigungssysteme
Bogenstraße 43 - 45
22926 Ahrensburg
Germany

Weitere Informationen
erhalten Sie unter:
Phone: +49 (0) 41 02 78 - 444
Fax +49 (0) 41 02 78 - 270
eMail: info@bea-group.com
www.Bea-Group.com

BeA is a member of the following associations:

