

Gas operated anchor nailer AN34/60-G642E

12100700



More details:



Fastener type

KMR Anchor nails P34°
· Diameter: 4 mm

Product strengths

- Battery indicator
- Includes transport case
- Integrated rafter holder
- Li-ion battery

Scope of operation

Carpentry, Dry and interior extension, Timber construction, Timber frame construction, Wooden constructions


Scope of delivery

Battery charger, Li-Ion Battery, Transport case, User manual

Technical data

EAN	4045758121092
Type of fastener	KMR Anchor nails P34°
Fastener diameter min	4 mm
Fastener diameter max	4 mm
Fastener length min	40 mm
Fastener length max	60 mm
Weight	4,02 kg
Driving system	Battery and combustion chamber
Activation method	Single activation
Tool length	425 mm
Tool width	108 mm
Tool height	393 mm
Impacts (for fuel cell)	1200
Hits per battery charge	8000
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	101,2 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	107,3 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	2,28 m/s ²
Vibration value Ka according to ISO 8662	1,12 m/s ²
Weight incl. packaging	6,6 kg

Related fastener



KMR Anchor nails P34°

- Diameter: 4 mm
- Length: 40 - 60 mm

Item No.	Diameter x Length	Nail shank	Material
10401923	4 mm x 40 mm	Smooth shank	Steel, galvanized
10401924	4 mm x 50 mm	Smooth shank	Steel, galvanized
10401925	4 mm x 60 mm	Smooth shank	Steel, galvanized

Other variations and sizes on request