

## Gas operated D-head nailer D34/90-G641E

12100699



More details:



### Fastener type

KMR Nail strips P34° D head  
· Diameter: 2,8 - 3,1 mm

### Product strengths

- Adjustable depth setting
- Anti-slip nose
- Battery indicator
- Includes transport case

### Scope of operation

Carpentry, Farming, woods and forestry, Measurement and assembly construction, Roofing and facade, Timber


### Scope of delivery

Battery charger, Li-Ion Battery, Transport case, User manual

## Technical data

EAN	4045758121085
Type of fastener	KMR Nail strips P34° D head
Fastener diameter min	2,8 mm
Fastener diameter max	3,1 mm
Fastener length min	50 mm
Fastener length max	90 mm
Weight	3,68 kg
Driving system	Battery and combustion chamber
Activation method	Single activation
Tool length	382 mm
Tool width	108 mm
Tool height	377 mm
Battery type	Li-ion
Impacts (for fuel cell)	1200 shots
Hits per battery charge	8000 shots
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	96,2 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	101 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	2,67 m/s <sup>2</sup>
Weight incl. packaging	7,8 kg

## Related fastener




## KMR Nail strips P34° D head

- Diameter: 2,8 - 3,1 mm
- Length: 50 - 90 mm

Item No.	Diameter x Length	Nail shank	Material
10401599	2,8 mm x 64 mm	Smooth shank	Steel, bright
10401600	2,8 mm x 64 mm	Ring shank	Steel, bright
10401601	2,8 mm x 64 mm	Ring shank	Steel, galvanized
10401602	2,8 mm x 70 mm	Smooth shank	Steel, bright
10401604	2,8 mm x 75 mm	Ring shank	Steel, bright
10401605	2,8 mm x 75 mm	Ring shank	Steel, galvanized
10401606	2,8 mm x 80 mm	Smooth shank	Steel, bright
10401607	2,8 mm x 80 mm	Ring shank	Steel, bright
10401608	2,8 mm x 80 mm	Ring shank	Steel, galvanized
10401609	3,1 mm x 80 mm	Smooth shank	Steel, bright
10401611	3,1 mm x 90 mm	Smooth shank	Steel, bright
10401612	3,1 mm x 90 mm	Smooth shank	Steel, galvanized
10401614	3,1 mm x 90 mm	Ring shank	Steel, hot-dip galvanized
10401654	2,8 mm x 64 mm	Smooth shank	Steel, galvanized
10401703	2,8 mm x 70 mm	Smooth shank	Steel, galvanized
10401704	2,8 mm x 80 mm	Smooth shank	Steel, galvanized
10401705	3,1 mm x 80 mm	Smooth shank	Steel, galvanized
10401706	3,1 mm x 83 mm	Smooth shank	Steel, galvanized
10401710	2,8 mm x 75 mm	Smooth shank	Steel, bright
10401715	2,8 mm x 70 mm	Ring shank	Steel, bright
10401716	3,1 mm x 90 mm	Ring shank	Steel, bright
10401718	3,1 mm x 90 mm	Ring shank	Steel, galvanized
10401889	3,1 mm x 80 mm	Ring shank	Steel, galvanized
10401893	3,1 mm x 90 mm	Ring shank	Steel, bright
10401894	2,8 mm x 55 mm	Ring shank	Steel, galvanized
10401895	2,8 mm x 65 mm	Ring shank	Steel, galvanized
10401896	2,9 mm x 50 mm	Ring shank	Steel, bright

10401951	3,1 mm x 50 mm	Screw shank	Steel, galvanized
10401960	2,8 mm x 50 mm	Ring shank	Steel, galvanized
10401961	2,8 mm x 70 mm	Ring shank	Steel, galvanized
10401962	2,8 mm x 50 mm	Ring shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)
10401963	2,8 mm x 70 mm	Ring shank	Stainless Steel, (AISI 316, EN grade 1.4401, A4)

## Related fastener




## KMR Nail strips P34° D head

- Diameter: 2,8 - 3,1 mm
- Length: 50 - 90 mm

Item No.	Diameter x Length	Nail shank	Material
10401720	2,8 mm x 50 mm	Smooth shank	Steel, bright
10401721	2,8 mm x 64 mm	Smooth shank	Steel, bright
10401722	2,8 mm x 70 mm	Smooth shank	Steel, bright
10401723	2,8 mm x 80 mm	Smooth shank	Steel, bright
10401724	3,1 mm x 80 mm	Smooth shank	Steel, bright
10401725	3,1 mm x 90 mm	Smooth shank	Steel, bright
10401726	2,8 mm x 64 mm	Smooth shank	Steel, galvanized
10401727	2,8 mm x 70 mm	Smooth shank	Steel, galvanized
10401728	2,8 mm x 80 mm	Smooth shank	Steel, galvanized
10401729	3,1 mm x 80 mm	Smooth shank	Steel, galvanized
10401730	3,1 mm x 90 mm	Smooth shank	Steel, galvanized
10401731	2,8 mm x 64 mm	Ring shank	Steel, bright
10401732	2,8 mm x 70 mm	Ring shank	Steel, bright
10401733	2,8 mm x 75 mm	Ring shank	Steel, bright
10401734	2,8 mm x 80 mm	Ring shank	Steel, bright
10401735	3,1 mm x 90 mm	Ring shank	Steel, bright
10401736	2,8 mm x 64 mm	Ring shank	Steel, galvanized
10401737	2,8 mm x 70 mm	Ring shank	Steel, galvanized
10401738	2,8 mm x 75 mm	Ring shank	Steel, galvanized
10401739	2,8 mm x 80 mm	Ring shank	Steel, galvanized
10401740	3,1 mm x 90 mm	Ring shank	Steel, galvanized
10401926	3,1 mm x 80 mm	Ring shank	Steel, galvanized

## Related fastener



### KMR Nail strips P34° D head

- Diameter: 2,8 - 3,1 mm
- Length: 50 - 90 mm

Item No.	Diameter x Length	Nail shank	Material
10401765	2,8 mm x 50 mm	Smooth shank	Steel, bright
10401766	2,8 mm x 64 mm	Smooth shank	Steel, bright
10401767	2,8 mm x 70 mm	Smooth shank	Steel, bright
10401768	2,8 mm x 80 mm	Smooth shank	Steel, bright
10401770	3,1 mm x 90 mm	Smooth shank	Steel, bright
10401771	2,8 mm x 64 mm	Smooth shank	Steel, galvanized
10401772	2,8 mm x 70 mm	Smooth shank	Steel, galvanized
10401773	2,8 mm x 80 mm	Smooth shank	Steel, galvanized
10401774	3,1 mm x 80 mm	Smooth shank	Steel, galvanized
10401775	3,1 mm x 90 mm	Smooth shank	Steel, galvanized
10401776	2,8 mm x 64 mm	Ring shank	Steel, bright
10401777	2,8 mm x 70 mm	Ring shank	Steel, bright
10401778	2,8 mm x 75 mm	Ring shank	Steel, bright
10401779	2,8 mm x 80 mm	Ring shank	Steel, bright
10401780	3,1 mm x 90 mm	Ring shank	Steel, bright
10401781	2,8 mm x 64 mm	Ring shank	Steel, galvanized
10401782	2,8 mm x 70 mm	Ring shank	Steel, galvanized
10401783	2,8 mm x 75 mm	Ring shank	Steel, galvanized
10401784	2,8 mm x 80 mm	Ring shank	Steel, galvanized
10401785	3,1 mm x 90 mm	Ring shank	Steel, galvanized
10401929	2,9 mm x 50 mm	Ring shank	Steel, galvanized
10401931	2,9 mm x 76 mm	Ring shank	Steel, galvanized
10401932	3,1 mm x 90 mm	Ring shank	Steel, galvanized
10401933	2,9 mm x 65 mm	Ring shank	Steel, bright
10401934	2,9 mm x 76 mm	Ring shank	Steel, bright
10401935	2,9 mm x 80 mm	Ring shank	Steel, bright
10401936	2,9 mm x 50 mm	Smooth shank	Steel, bright

10401937	2,9 mm x 65 mm	Smooth shank	Steel, bright
10401938	2,9 mm x 70 mm	Smooth shank	Steel, bright
10401939	2,9 mm x 80 mm	Smooth shank	Steel, bright
10401940	2,8 mm x 80 mm	Ring shank	Steel, galvanized
10401941	3,1 mm x 90 mm	Smooth shank	Steel, bright
10401942	2,8 mm x 64 mm	Smooth shank	Steel, galvanized
10401943	2,8 mm x 70 mm	Smooth shank	Steel, galvanized
10401944	2,8 mm x 80 mm	Smooth shank	Steel, galvanized
10401945	3,1 mm x 80 mm	Smooth shank	Steel, galvanized
10401947	3,1 mm x 90 mm	Smooth shank	Steel, galvanized

**Other variations and sizes on request**