

## Anchor nailer 3734

12100655



More details:



### Fastener type

KMR Anchor nails P34°  
· Diameter: 4 mm

### Product strengths

· Security due to multi-blow technology

### Scope of operation

Carpentry, Timber construction, Timber frame construction,  
Wooden constructions


### Scope of delivery

Hex key, Operating instructions, Service oil, Sparepart list

## Technical data

EAN	4045759059776
Type of fastener	KMR Anchor nails P34°
Fastener diameter min	4 mm
Fastener diameter max	4 mm
Fastener length min	40 mm
Fastener length max	50 mm
Weight	1,9 kg
Driving system	Compressed air
Activation method	Contact activation
Air consumption per drive operation	3,3 l (7 bar)
Tool length	277 mm
Tool height	255 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	87,9 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	100,9 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	6,89 m/s <sup>2</sup>
Weight incl. packaging	3,75 kg

## Related fastener



KMR Anchor nails P34°

- Diameter: 4 mm
- Length: 40 - 50 mm

Item No.	Diameter x Length	Nail shank	Material
10401923	4 mm x 40 mm	Smooth shank	Steel, galvanized
10401924	4 mm x 50 mm	Smooth shank	Steel, galvanized

### Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website