

Pin nailer 3485

12100581



More details:



Fastener type

KMR Pins
· Diameter: 0,65 mm

Product strengths

· Practical belt hook
· Rubberized safety yoke

Scope of operation

Dry and interior extension, Joinery, Measurement and assembly construction, Window and door construction


Scope of delivery

Additional handhold, Exploded drawing, Hex key, Service Instructions, Service oil, Sparepart list

Technical data

EAN	4045759054320
Type of fastener	KMR Pins
Fastener diameter min	0,65 mm
Fastener diameter max	0,65 mm
Fastener length min	25 mm
Fastener length max	50 mm
Weight	1,23 kg
Driving system	Compressed air
Activation method	Single activation
Operating pressure min	5 bar
Operating pressure max	7 bar
Air consumption per drive operation	0,76 l (7 bar)
Tool length	256 mm
Tool height	243 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	78,9 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	89,7 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	1,43 m/s ²
Weight incl. packaging	2,2 kg

Related fastener



KMR Pins

- Diameter: 0,65 mm
- Length: 25 - 50 mm

Item No.	Length	Point type	Material
10100223	0,65 mm x 25 mm	Chisel point	Bronze
10100224	0,65 mm x 30 mm	Chisel point	Bronze
10100225	0,65 mm x 35 mm	Chisel point	Bronze
10100226	0,65 mm x 40 mm	Chisel point	Bronze
10100227	0,65 mm x 45 mm	Chisel point	Bronze
10100228	0,65 mm x 50 mm	Chisel point	Bronze

Other variations and sizes on request

Access all Declarations of Performance (DoPs) and CE-Label on our website