

## Gas operated metal connector nailer R20/35-

12100708



### Fastener type

KMR Nail strip Mini K20°  
· Diameter: 2,5 - 2,8 mm

### Product strengths

- Adjustable depth setting
- Anti-slip nose
- Li-ion battery
- Practical belt hook

### Scope of operation

Carpentry, Roofing and facade, Timber construction

### Scope of delivery

Battery charger, Li-Ion Battery, Transport case, User manual

More details:



## Technical data


|  |                                |
|--|--------------------------------|
| EAN  | 4045758121511                  |
| Type of fastener   | KMR Nail strip Mini K20°       |
| Fastener diameter min                                    | 2,5 mm                         |
| Fastener diameter max                                    | 2,8 mm                         |
| Fastener length min                                      | 22 mm                          |
| Fastener length max                                      | 35 mm                          |
| Weight   | 2,5 kg                         |
| Driving system   | Battery and combustion chamber |
| Activation method  | Single activation              |
| Tool length  | 327 mm                         |
| Tool width   | 137 mm                         |
| Tool height  | 310 mm                         |
| Battery type   | Li-ion                         |
| Battery capacity   | 2500 Ah                        |
| Battery voltage  | 72 V                           |
| Impacts (for fuel cell)                                  | 1200                           |
| Hits per battery charge                                  | 8000                           |
| Declaration of conformity                                | CE, EAC, UKCA                  |
| Noise characteristic L pA, 1s according to EN 12549      | 95,8 dB(A)                     |
| Noise characteristic L WA, 1s, d according to EN 12549   | 97,8 dB(A)                     |
| Noise characteristic K pA and K WA according to EN 12549 | 2,5 dB(A)                      |
| Vibration value ahd according to ISO 8662                | 1,84 m/s <sup>2</sup>          |

**Technical data**

Weight incl. packaging

5,6 kg

## Related fastener



## KMR Nail strip Mini K20°

- Diameter: 2,8 mm
- Length: 25 - 32 mm

| Item No. | Diameter x Length | Nail shank   | Material  |
|----------|-------------------|--------------|---|
| 10401456 | 2,8 mm x 31 mm    | Smooth shank | Copper  |
| 10401457 | 2,8 mm x 31 mm    | Smooth shank | Steel, hot-dip galvanized                       |
| 10401460 | 2,8 mm x 25 mm    | Smooth shank | Steel, hot-dip galvanized                       |
| 10401958 | 2,8 mm x 32 mm    | Ring shank   | Steel, hot-dip galvanized                       |
| 10401959 | 2,8 mm x 32 mm    | Ring shank   | Steel, galvanized                               |
| 10402043 | 2,8 mm x 25 mm    | Ring shank   | Stainless Steel (AISI 304, EN grade 1.4301, A2) |

**Other variations and sizes on request**