

Gas operated concrete nailer CN40-G643E

12100701



More details:



Fastener type

KMR Concrete Nails CN
· Diameter: 2,6 - 3 mm

Product strengths

- Adjustable depth setting
- Battery indicator
- Includes transport case
- Li-ion battery

Scope of operation

Concrete building, Dry and interior extension

Scope of delivery

Battery charger, Li-Ion Battery, Transport case, User manual

Technical data

EAN	4045758121108
Type of fastener	KMR Concrete Nails CN
Fastener diameter min	2,6 mm
Fastener diameter max	3 mm
Fastener length min	15 mm
Fastener length max	40 mm
Weight	3,8 kg
Driving system	Battery and combustion chamber
Activation method	Single activation
Tool length	327 mm
Tool width	130 mm
Tool height	385 mm
Battery type	Li-ion
Battery capacity	2500 Ah
Battery voltage	72 V
Impacts (for fuel cell)	1200
Hits per battery charge	8000
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	101,5 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	104,1 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	2,83 m/s ²

Technical data

Vibration value Ka according to ISO 8662	1,37 m/s ²
Weight incl. packaging	7,6 kg

Related fastener

**KMR Concrete Nails CN**

- Diameter: 2,6 mm
- Length: 15 - 40 mm

Item No.	Diameter x Length	Nail shank	Material
10401744	2,6 mm x 15 mm	Smooth shank	Steel, bright
10401745	2,6 mm x 20 mm	Smooth shank	Steel, bright
10401746	2,6 mm x 25 mm	Smooth shank	Steel, bright
10401747	2,6 mm x 30 mm	Smooth shank	Steel, bright
10401748	2,6 mm x 35 mm	Smooth shank	Steel, bright
10401749	2,6 mm x 40 mm	Smooth shank	Steel, bright

Other variations and sizes on request